

HYBRID SERIES

Split Phase

LXP-LB-US 12k

- AC coupling function
- Peak shaving function
- Smart load control
- Support up to 10pcs in parallel
- 12kW UPS output split phase
- LCD color touch screen
- 3 MPPT inputs, maximum up to 18 kW
- Breakers (Load and battery) are integrated
- 200A AC bypass current
- Separate generator interface available
- Integrated UPS module, on/off grid seamless switching under 20ms



Specification

LXP-LB-US 12k	
Max. PV array power(W)	18000
Rated PV input voltage(V)	360
Number of independent MPPT inputs	3
PV input voltage range(V)	100~600
MPPT voltage range(V)	120~500
Start-up voltage(V)	140
Max. PV input current per MPPT(A)	25/15/15
Max. PV short-circuit current input per MPPT(A)	31/19/19
Battery	
Compatible battery type	Lithium-ion/Lead-Acid
Rated battery voltage(V)	48
Battery voltage range(V)	40~60
Max. charging/discharging current(A)	250
Max. charging/discharging power(W)	12000
Force wake up battery from PV function	YES
Grid	
Rated AC voltage(V)	240/208
Rated AC frequency(Hz)	60
Rated AC output current(A)	50
Rated AC output power(W)	12000
Max. AC input current(A)	200
PF	0.99 (Adjustable from 0.8 leading to 0.8 lagging)
THDI	<3%
Rated AC current of BYPASS relays(A)	200
UPS	
Rated output power(W)	12000
Rated output voltage(V)	120/240; 120/208
Rated output current(A)	50
Rated output frequency(Hz)	60
Surge power, duration	2Pn, 0.5s
Switching time	20ms
Wave form	Sine wave
THDV	<3%
Efficiency	
Max. MPPT efficiency	99.9%
Max. efficiency	97.5%
Battery charging/discharging efficiency	94.0%
CEC efficiency	96.9%
Protection	
PV reverse polarity protection	YES
Over current/voltage protection	YES
Anti-islanding protection	YES
AC Short-circuit protection	YES
Leakage current protection	YES
DC switch	YES
AC/DC surge protection Type III	YES
Rapid shut down	YES
Grid/AFCI/RSD monitoring	YES
Load switch(Current)	200A
Battery switch(Current/Voltage)	2*200A/80V
General	
Dimensions(W*H*D)	520*870*285mm/20.5*34.2*11.2inch
Weight	55kg/121.2lbs
Ingress protection rating	IP65/ NEMA 4X
Relative humidity	0~100%
Operating environment temperature range	-25~60°C, >45°C Derating
Storage temperature range	-25~60°C
Display & Communication interface	Touch color screen, RS485/Wi-Fi/CAN
Warranty	5/10 years
Cooling method	Smart Cooling
Topology	Transformer-less
Altitude	<2000m
Standards & Certification	
E5000, SA17-18, SA2018, CSA STD. C22.2 No.107.1 and 330, UL STD.1741, 1741SB, UL1998:2018 IEEE STD.1547 and 1547.1, IEEE STD. HECO SRD-IEEE-1547.1, ETL, CETL, America CEC List, NEC. section690.12, FCC, CEC, UL9540, CSA STD. C22.2 No.107.1, UL STD.1741, 1741SB	