


HYBRID SERIES

GEN-HB-US 25K (High Voltage)

- 120/240 split-phase output 25kW
- 6 MPPTs with 8 strings, Max. 48kW PV input
- Working with High Voltage Battery
- Whole House Backup with 200A Output
- Supports up to 6 units in Parallel
- Optimized for Small C&I and High Energy Demand Households



Model	GEN-HB-US 25K
Input(PV DC)	
Max. PV input power (W)	48000
Rated PV input voltage (V)	360
Number of independent MPPT inputs	6 (A:2 / B:2 / C:1 / D:1 / E:1 / F:1)
Max. PV input voltage (V)	550
MPPT voltage range (V)	120 ~ 480
Start-up voltage (V)	120
Max. PV input current per MPPT (A)	34 / 34 / 17 / 17 / 17 / 17
Max. PV short-circuit current input per MPPT (A)	50 / 50 / 30 / 30 / 30 / 30
Battery	
Compatible battery type	Lithium-ion / Lead-Acid
Rated battery voltage (V)	307.2
Battery voltage range (V)	120 ~ 454.4
Max. charging/discharging current (A)	100
Max. charging/discharging power (W)	25000
Force wake up battery from PV function	YES
Grid	
Rated AC voltage (V)	120 / 240, 120 / 208
Rated AC frequency (Hz)	50 / 60
Rated AC output current (A)	104
Rated AC output power (W)	25000
Max. AC input current (W)	108A
PF	0.99 (Adjustable from 0.8 leading to 0.8 lagging)
THDI	< 5%
Max. continuous AC passthrough current (A)	104A / Split; Bypass 200A
GEN	
Rated GEN voltage (V)	120 / 240, 120 / 208
Rated GEN frequency (Hz)	50 / 60
Rated GEN input current (A)	104
Rated GEN input power (W)	25000
EPS Output - with Battery	
Rated output power (W)	25000
Rated output voltage (V)	120 / 240, 120 / 208
Rated output current (A)	104
Rated output frequency (Hz)	50 / 60
Surge power, duration	2 × rated power for 10s
Switching time	< 15 ms
Wave form	Sine wave
THDV	< 3%
Efficiency	
MPPT efficiency	98.0%
Max. efficiency	94.0%
Max. charge/discharge efficiency	96.0%
Protection	
Anti-islanding Protection	YES
AC Short-circuit Protection	YES
Leakage Current Protection	YES
Grid Monitoring	YES
PV DC Switch	YES
Grid/Load/Generator/Smart Load Breaker integrated	YES
Battery/PV reverse polarity protection	YES
Over Current/Voltage Protection	YES
PV Insulation Detection	YES
Battery Soft Start Protection	YES
SPD Protection	YES
AFCI/RSD protection	YES
GFCI	YES
General	
Dimensions (W × H × D)	626 × 924 × 285 mm / 24.7 × 36.4 × 11.2 in
Weight	73 kg / 160.94 lbs
Ingress protection rating	IP65 / NEMA 4X
Display	LCD
Topology	Transformer-less
Ambient Temperature Range	-25 ~ 60°C (> 45°C, output derating)
Standby Losses	10W Sleep Mode, 30W Standby Mode
Cooling	Smart Cooling
Relative Humidity Range	0 ~1 00%
Max. Operating Altitude (m)	2000
Noise emission (dB)	55
Communication from Inverter	SunSpec Modbus RTU over RS485, RJ45 for ext Wifi Dongle
Standards & Certification	
UL 1741SA, UL 1741SB, CSA C22.2, CEC, IEEE 1547.1, HECO SRD V2.0	