

## Battery Storage

# PGEM MAX



## Features

-  35 units stackable
-  200A continuous current
-  Ultra safe LFP material  
10 years warranty with 8000cycles
-  Flexible remote upgrade
-  Smart BMS management for longer lifespan
-  Multi protection to avoid over discharge  
Short circuit protection
-  Active balancing charging, low self consumption
-  Stackable, floor-standing, wall-mount, with wheels or foot brackets options
-  Fire suppression built in

Model	PGEM MAX
Cell Type	LFP
Rated Energy	16.076kWh
Rated Capacity	314Ah
Rated Voltage	51.2V
Charge Voltage	56.5V
Battery Charge Current	165A (Max. continuous) 170A (Start limit current to 10A, retest every 10min) 180A (Peak1 15s) 200A (Peak2 500ms)
Battery DisCharge Current	200A (Max. continuous) 205A (Start giving over-current alarm but not stop discharging) 210A (Peak1 2min) 220A (Peak2 500ms)
Parallel	Up to 35 units parallelable w/o extra device needed, slave battery drops offline or come back alive does not affect system running
IP Level	IP20
Dimension (W × D × H)	900 × 445 × 230 mm / 35.4 × 17.5 × 9.1 in
Weight	120 kg / 264.6 lbs
Communication	CAN / RS485
Robust Applications	Auto-addressing and stronger protection
DOD	90%
Cycles	8000
Humidity	5% ~ 85%RH (No condensation)
Work Temperature	-20 ~ +55°C
Remote Maintenance	Flexible remote upgrade, Original firmware backup to prevent upgrade failure
Warranty *	10 years, 8000 cycles
Certification	CE; UN38.3; IEC62619
Protection	Overcharge/discharge/current/voltage/temperature protection Short circuit protection, Reverse connection protection Charge balance, Low SOC protection

@25°C, 90% DOD. 0.5C testing condition