

HYBRID SERIES

GEN2-LB-EU 7-14K (Single-Phase)

- 3 MPPTs with 3 strings, Max. PV input 18kW
- Max. charging and discharging current: 250A
- Supports up to 10pcs in parallel for on/off grid
- AI-Driven optimization mode for e-bill reduction
- Separate port for
 - Generator connection
 - Auto generator control
 - Support generator exercise
 - Support generator boost function
 - Or smart load connection and auto control
 - Or AC coupling function



Model	GEN2-LB-EU 7K	GEN2-LB-EU 8K	GEN2-LB-EU 10K	GEN2-LB-EU 12K	GEN2-LB-EU 14K
Input (PV DC)					
Max. PV input power (W)	12000		15000	18000	
Rated PV input voltage (V)	340				
Number of independent MPPT inputs	3 / (1:1:1)				
Max. PV input voltage (V)	550				
MPPT voltage range (V)	120 ~ 440				
Start-up voltage (V)	100				
Max. PV input current per MPPT (A)	26 / 15 / 15				
Max. PV short-circuit current input per MPPT (A)	31 / 18 / 18				
Battery					
Compatible battery type	Lithium-ion / Lead-Acid				
Rated battery voltage (V)	48				
Battery voltage range (V)	40 ~ 60				
Max. charge / discharge current (A)	147	167	210	250	
Max. charge / discharge power (W)	7000	8000	10000	12000	
Force wake up battery from PV function	YES				
Grid					
Rated AC voltage (V)	230				
Rated AC frequency (Hz)	50 / 60				
Rated AC output current (A)	30.5	35	43.5	52	61
Rated AC output power (W)	7000	8000	10000	12000	14000
Acceptable input voltage range (V)	180 ~ 270				
Max. AC input current (A)	100				
Max. AC input power (W)	18000				
PF	0.99 (Adjustable from 0.8 leading to 0.8 lagging)				
THDI	< 5%				
Max continuous AC passthrough current (A)	100				
GEN					
Rated GEN voltage (V)	230				
Rated GEN frequency (Hz)	50 / 60				
Rated GEN input current (A)	80				
Rated GEN input power (W)	18000				
UPS					
Rated output power (W)	7000@230V	8000@230V	10000@230V	12000@230V	
Rated output voltage (V)	230				
Rated output current (A)	30.5	35	43.5	52	
Rated output frequency (Hz)	50 / 60				
Surge power, duration	2 × rated power for 0.5s				
Switching time (UPS)	Single: 10ms / Parallel: 20ms				
Wave form	Sine wave				
THDV	< 3%				
Efficiency					
MPPT efficiency	99.9%				
Max. charge / discharge efficiency	95.0%				
Protection					
Over current / voltage protection	YES				
AC short-circuit current protection	YES				
Grid monitoring	YES				
DC switch	YES				
AC / DC surge protection	Type III				
General					
Dimensions (W × H × D)	566 × 653 × 275 mm / 22.3 × 25.7 × 10.8 in				
Weight	48 kg / 105.8 lbs				
Ingress protection rating	IP66				
Relative humidity	0 ~ 100%				
Operating environment temperature range (°C)	-25 ~ 60 °C, > 45 °C Derating				
Storage temperature range (°C)	-25 ~ 60				
Display & Communication interface	Touch color screen, RS485 / Wifi / CAN				
Warranty	5 / 10 years				
Cooling method	Smart cooling				
Topology on AC / battery side	Transformerless / Transformer				
Max. operating altitude (m)	2000				
Noise emission (dB)	55				
Standard & Certification					
PTPIREE TypeA, EN 62109-1/EN 61000, G100/G99					